

Evalox303DG

clear anti dusting sealer for cement & concrete surfaces

Description & Uses:

Evalox303DG seals and hardens new/old concrete and cement floors whilst providing greatly increased resistance to abrasion which causes dusting. It leaves a thin seal over the surface, which makes cleaning easier. Suitable for interior & exterior use – for light, medium and heavy duty application

Method of Application:

Evalox303DG is supplied ready-for-use and no thinning is required.

Easily brushed or sprayed on.

Do not apply if temperature is below 10°C or likely to fall below 10°C and below the dew point temperature during drying.

Do not apply if rain is expected or in extreme hot dry conditions.

Do not apply if the substrate temperature is 10C or less.

Surface preparation:

Ensure that areas/surfaces to be sealed are completely free of dirt, grease, grime, oil, cement, excess grout, mould etc. Use a good quality water-based degreaser like Evaklenz604WB.

Application procedure:

1. Evenly apply - ensuring that the surface is completely & uniformly covered. Leave to dry.
2. ONLY 1 coat is required – however highly porous surfaces will require a further coat.

Clean up:

Use clean water & detergent to wash up all tools

Coverage:

Approximately 13sqm per lt.

Coverage will vary depending on the profile and porosity of the surface.

Drying time: approx. 2 hrs

Pack size: 5lt polycans

Colour of liquid:

- Wet state: Milky white
- Finish: Clear



VOC:

<30g/lt

Safety & First Aid:

Keep out of reach of children.

Wear protective clothing.

Eye Contact - rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.

If Swallowed - drink large amounts of water and seek medical attention.

Shelf life & Storage:

1 year in original, unopened container.

Store in a dry area between 5°C and 40°C - Protect from direct unlight.

Environment:

Always recycle when able to.

Technical Information:

We provide free comprehensive technical back-up service on all of our products and we guarantee that our products will comply with the technical properties detailed in their specific Technical Data Sheets issued by ourselves.

To the best of our knowledge and belief, this information is true and accurate. As the conditions of use and any labour involved are beyond our control, the end-user must satisfy himself by prior testing that the product is suitable for his specific application.

Products are sold subject to our Standard Conditions of Sale.

Evachem Construction Chemicals (Pty) Ltd

PO Box 1159, Wandsbeck, 3630 | 4 Dinkelman Road, New Germany, 3610

Tel: 0861 EVACHEM / 0861 382 2436 | Fax: 031705 3884

info@evachem.co.za - www.evachem.co.za